



General Specifications

Characteristics	Engineered
Description	Engineered prefinished hardwood flooring with tongues and grooves 4 sides micro bevelled
Thickness	14mm (sawn hardwood veneer 3mm)
Width	190mm
Length	1900mm
Installation	Floating/Glue down
Subfloor	Wood, concrete or radiant heat system
Species	White Oak
Grade	AB/ABC/ABCD
Color Choice	Check consult the Product Chart
Finish	Matt finish UV Protection: All products
Applicable Standards	E1 Floor-Score SGS VOC PEFC (Certificate No. RINA-PEFEC-COC-83)
Provenance	Made in Dalian, China
Warranty	Structural lifetime limited warranty - 25 years for residential warranty (Relative humidity must always be maintained within a range of 25% and 70%)
Packaging	1900mm
Content of a box	31.09 sqft (2.888m ²)
Size of a box	75.5"L x 8"W x 4.6"H
Weight of a box	40 to 49 lbs
Content of a pallet	45 boxes
Size of a pallet	75.5"L x 39.79"W x 41.13"H
Relative Species Hardness	
NWFA Janka Test Hardness Test(ASTM-D-143) Red Oak 1,290 lbs* -100% *lbs = Applied force in pounds	OAK 1290 lbs - average harness PINE 1290 lbs - average harness

Please refer to values in millimeters to get the exact planks length.